

AVR

AUTOMATIC VOLTAGE REGULATOR

全電子式穩壓器



FEATURES:

- MICRO SIZE
- SURGE PROTECTION
- COMPACT AND RELIABLE
- HIGH EFFICIENCY 97%~99%
- HIGH POWER FACTOR 0.98~1
- OVER LOAD/SHORT PROTECTION

APPLICATIONS:

- | | |
|-----------------------------------|-------------------------|
| ● PERSONAL COMPUTER | ● PRODUCTION LINE |
| ● LASER PRINTER | ● INSTRUMENT |
| ● CASH REGISTER | ● COPY/PRINTING DEVICE |
| ● ATM | ● POS TERMINAL |
| ● OA EQUIPMENT | ● ALARM/SECURITY SYSETM |
| ● HOUSEHOLD ELECTRICAL APPLIANCES | |

穩壓、可靠、無干擾、體積小、重量輕

AUTOMATIC VOLTAGE REGULATOR

全電子式穩壓器

ND-500
ND-1000
ND-1500



ND-500M
ND-1000M
ND-1500M



ND-500C
ND-1000C
ND-1500C



NR-750
NR-1200
NR-2000

TECHNICAL SPECIFICATIONS(技術規格)

MODEL (型號)		ND-500	ND-1000	ND-1500	NR-750	NR-1200	NR-2000
		ND-500M	ND-1000M	ND-1500M			
		ND-500C	ND-1000C	ND-1500C			
CAPACITY (容量)		500VA/400W	1KVA/800W	1.5KVA/1.2KW	750VA/600W	1.2KVA/960W	2KVA/1.6KW
INPUT (輸入)	VOLTAGE (電壓)	110V OR 220V± 14%			110V OR 220V± 20%		
	FREQUENCY (頻率)	47HZ-63HZ					
	POWER FACTOR (輸入功因)	>0.98					
OUTPUT (輸出)	REGULATION (穩壓率)	≤6%			≤5%		
	RESPONSE TIME (反應時間)	<1 CYCLE(週波)					
	DISTORTION (失真率)	NO DISTORTION,THE SAME AS INPUT WAVEFORM (和輸入波形相同無失真)					
EFFICIENCY (效率)		>97%					
PROTECTION (保護)	OVERLOAD & SHORT (過載和短路)	CIRCUIT BREAKER (過載保護器)					
	SURGE (突波)	VARISTOR CLAMPING 107 JOULES(2ms),4500A(8/20us) (突波吸收器吸收107焦耳(2ms),4500安培(8/20us))					
OUTPUT SOCKET (輸出插座)		NEMA5-15Rx2 OR THE OTHER TYPE (美式2個或其他指定插座)			NEMA5-15Rx4 OR THE OTHER TYPE (美式4個或其他指定插座)		
INDICATOR (指示燈)		LED					
O/P VOLTAGE METER (輸出電壓錶)	×-WITHOUT (無)	×	×	×	×		
	✓-WITH (有)	✓	✓	✓			
		×	×	×			
OPERATING TEMP (工作溫度)		0~40 °C					
NET WEIGHT 淨重(KGS)		1.6	2	2.4	3.7	4.7	5.8
DIMENSION (尺寸)	WxHxD(mm) 寬x高x深	109x82x210			89x170x266		
		109x82x210					
		79x112x172					

ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

本公司產品不斷改進，規格變更恕不另行通知。