## **FEATURES:**

- Easy Installation and Repair
- UPS + Emergency Light Function
- Cold Start Function
- Low Battery Voltage Alarm
- Low Battery Cut-off Automatically
- Option for External Battery Bank
- Option for AVR Function

- Manual Selection for 110V or 220V System
- Over 32 Hours Standby time
- Smart Battery Testing
- Smart Overload and Short Circuit Protection
- Powerful Start Capacity
- Auto Transfer to Battery Mode by Timer
- No Load Automatic Shutdown by Timer



## **SPECIFICATIONS**

| Model                  |                       | D750  | D1000              | D1500              |
|------------------------|-----------------------|---|--------------------|--------------------|
| Motor Power Rating     |                       | 1/4 HP 300KG max.   | 1/2 HP 550KG max.  | 1HP 1000KG max.    |
| OUTPUT                 | Capacity              | 750VA / 450W  | 1000VA / 600W      | 1500VA / 900W      |
|                        | Start Capacity        | 2KVA  | 3KVA               | 4.5KVA             |
|                        | Voltage               | Same as Input Nominal   |                    |                    |
|                        | Regulation            | Vrms±5%   |                    |                    |
|                        | Frequency             | 50/60 HZ  |                    |                    |
|                        | Waveform PWM Stepwave |   |                    |                    |
| INPUT                  | Voltage               | 110/220V Selectable   |                    |                    |
|                        | Frequency             | 50/60 HZ±3 HZ   |                    |                    |
| BATTERY                | Battery Voltage       | 24VDC   | 24VDC              | 24VDC              |
|                        | Spec. / pcs           | 12V8.0AH / 2 pcs  | 12V 7.2AH / 4 pcs  | 12V8.0AH / 4 pcs   |
|                        | Type                  | Lead-acid Maintenance Free  |                    |                    |
| PROTECTION             | Over Voltage          | YES   |                    |                    |
|                        | Under Voltage         | YES   |                    |                    |
|                        | Surge                 | Line Filter & Surge Suppression Meet IEEE-587, Cat. A   |                    |                    |
|                        | Noise                 | Varistor Clamping 150 Joules. Response Greater than 20dB and over 1 MHZ Range for Common & Transverse Modes   |                    |                    |
|                        | Overload              | Fuse & Current Limited & Cut-off  |                    |                    |
|                        | Short Circuit         | Fuse, Current Limited   |                    |                    |
|                        | Low Battery           | Battery No Battery Drain after Cut-off  |                    |                    |
| INDICATOR              | Audible               | Beeping Alarm; Low Battery and Overload   |                    |                    |
|                        | Visible               | AC SW LED Indicate; AC SW On→Light; AC SW Off→Dark<br>220V LED Indicate; 220V System→Light; 110V System→Dark<br>CPU LED Indicate; Normal→Slow; Start Timer→Fast |                    |                    |
| COLD START             |                       | Without AC Present, Force UPS by Pushing Reset Switch   |                    |                    |
| EMERGENCY LIGHT OUTLET |                       | Install a Light. It will Light while AC Failure   |                    |                    |
| ENVIRNOMENT            | Temperature           | 0-40 degree C   |                    |                    |
|                        | Humidity              | 0-90% Non-condensing  |                    |                    |
| MECHANICAL             | Dim.WxHxD             | 302 x 265 x 150 mm  | 352 x 315 x 156 mm | 352 x 315 x 156 mm |
|                        | Weight (kgs)          | 15.0  | 20.0               | 25.0               |
| SUITABLE               |                       | Electric Rolling Door, Motor, PC, TV, Radio, Fax, Bulb  |                    |                    |

<sup>\*</sup> The above specification is subject to change without prior notice

<sup>\*\*</sup> All trade names mentioned are the properties of their respective owners